



# Zytel® PLS95G35DH1 NC010 (PRELIMINARY)

## ZYTEL® PLUS NYLON RESIN

Common features of Zytel® nylon resin include mechanical and physical properties such as high mechanical strength, excellent balance of stiffness and toughness, good high temperature performance, good electrical and flammability properties, good abrasion and chemical resistance. In addition, Zytel® nylon resins are available in different modified and reinforced grades to create a wide range of products with tailored properties for specific processes and end-uses. Zytel® nylon resin, including most flame retardant grades, offer the ability to be coloured.

The good melt stability of Zytel® nylon resin normally enables the recycling of properly handled production waste. If recycling is not possible, DuPont recommends, as the preferred option, incineration with energy recovery (-31kJ/g of base polymer) in appropriately equipped installations. For disposal, local regulations have to be observed.

Zytel® nylon resin typically is used in demanding applications in the automotive, furniture, domestic appliances, sporting goods and construction industry.

Zytel® PLS95G35DH1 NC010 is a high flow, 35% glass fibre reinforced, DuPont™ SHIELD protected polyamide resin for injection moulding. It provides excellent surface appearance, excellent welding, excellent fatigue retention and exceptional resistance to hot air and hot oil.

### Product information

Resin Identification	PA66/6T-GF35	ISO 1043
Part Marking Code	>PA66/6T-GF35<	ISO 11469
ISO designation	ISO 16396-PA66/6T,GF35,M1GHNR,S12-110	

### Rheological properties

	dry/cond.		
Viscosity number	125/*	cm <sup>3</sup> /g	ISO 307, 1157, 1628
Moulding shrinkage, parallel	0.1/-	%	ISO 294-4, 2577
Moulding shrinkage, normal	0.6/-	%	ISO 294-4, 2577

### Typical mechanical properties

	dry/cond.		
Tensile Modulus	11000/8000	MPa	ISO 527-1/-2
Stress at break	209/148	MPa	ISO 527-1/-2
Strain at break	3.1/5.4	%	ISO 527-1/-2
Charpy impact strength, 23°C	80/100	kJ/m <sup>2</sup>	ISO 179/1eU
Charpy notched impact strength, 23°C	12/14	kJ/m <sup>2</sup>	ISO 179/1eA
Ball indentation hardness, H 961/30	285/-	MPa	ISO 2039-1
Poisson's ratio	0.34/0.34	-	



# Zytel® PLS95G35DH1 NC010 (PRELIMINARY)

## ZYTEL® PLUS NYLON RESIN

### Thermal properties

	dry/cond.		
Melting temperature, 10°C/min	269/*	°C	ISO 11357-1/-3
Glass transition temperature, 10°C/min	65/-	°C	ISO 11357-1/-2
Temp. of deflection under load, 1.8 MPa	249/*	°C	ISO 75-1/-2

### Flammability

	dry/cond.		
Burning Behav. at 1.5mm nom. thickn.	HB/*	class	IEC 60695-11-10
Thickness tested	1.5/*	mm	IEC 60695-11-10
FMVSS Class	B	-	ISO 3795 (FMVSS 302)
Burning rate, Thickness 1 mm	25	mm/min	ISO 3795 (FMVSS 302)

### Electrical properties

	dry/cond.		
Comparative tracking index	600/-		IEC 60112

### Other properties

	dry/cond.		
Humidity absorption, 2mm	1.8/*	%	Sim. to ISO 62
Water absorption, 2mm	6/*	%	Sim. to ISO 62
Density	1430/-	kg/m <sup>3</sup>	ISO 1183

### Injection

Drying Recommended	yes
Drying Temperature	80 °C
Drying Time, Dehumidified Dryer	2 - 4 h
Processing Moisture Content	≤0.2 %
Melt Temperature Optimum	285 °C
Min. melt temperature	280 °C
Max. melt temperature	290 °C
Max. screw tangential speed	0.2 m/s
Mold Temperature Optimum	100 °C
Min. mould temperature	70 °C
Max. mould temperature	120 °C
Hold pressure range	50 - 100 MPa
Hold pressure time	3 s/mm
Ejection temperature	210 °C

### Characteristics


Additives	Release agent
-----------	---------------



# Zytel® PLS95G35DH1 NC010 (PRELIMINARY)

ZYTEL® PLUS NYLON RESIN

Viscosity-shear rate  
(measured on Zytel® PLS95G35DH1 BK549)






# Zytel® PLS95G35DH1 NC010 (PRELIMINARY)

ZYTEL® PLUS NYLON RESIN

Shearstress-shear rate  
(measured on Zytel® PLS95G35DH1 BK549)






# Zytel® PLS95G35DH1 NC010 (PRELIMINARY)

ZYTEL® PLUS NYLON RESIN

Stress-strain (dry)  
(measured on Zytel® PLS95G35DH1 BK549)






# Zytel® PLS95G35DH1 NC010 (PRELIMINARY)

ZYTEL® PLUS NYLON RESIN

Stress-strain (cond.)  
(measured on Zytel® PLS95G35DH1 BK549)






# Zytel® PLS95G35DH1 NC010 (PRELIMINARY)

ZYTEL® PLUS NYLON RESIN

Secant modulus-strain (dry)  
(measured on Zytel® PLS95G35DH1 BK549)






# Zytel® PLS95G35DH1 NC010 (PRELIMINARY)

ZYTEL® PLUS NYLON RESIN

Secant modulus-strain (cond.)  
(measured on Zytel® PLS95G35DH1 BK549)








# Zytel® PLS95G35DH1 NC010 (PRELIMINARY)

ZYTEL® PLUS NYLON RESIN

Tensile modulus-temperature (dry)  
(measured on Zytel® PLS95G35DH1 BK549)






# Zytel® PLS95G35DH1 NC010 (PRELIMINARY)

ZYTEL® PLUS NYLON RESIN

Tensile modulus-temperature (cond.)  
(measured on Zytel® PLS95G35DH1 BK549)





# Zytel® PLS95G35DH1 NC010 (PRELIMINARY)

## ZYTEL® PLUS NYLON RESIN

### Chemical Media Resistance

#### Acids

- ✓ Acetic Acid (5% by mass), 23°C
- ✓ Citric Acid solution (10% by mass), 23°C
- ✓ Lactic Acid (10% by mass), 23°C

#### Symbols used:

- ✓ possibly resistant  
Defined as: Supplier has sufficient indication that contact with chemical can be potentially accepted under the intended use conditions and expected service life. Criteria for assessment have to be indicated (e.g. surface aspect, volume change, property change).
- ✗ not recommended - see explanation  
Defined as: Not recommended for general use. However, short-term exposure under certain restricted conditions could be acceptable (e.g. fast cleaning with thorough rinsing, spills, wiping, vapor exposure).

The above data are preliminary and are subject to change as additional data are developed on subsequent lots.

The information set forth herein is furnished free of charge, is based on technical data that DuPont believes to be reliable, and represents typical values that fall within the normal range of properties. This information relates only to the specific material designated and may not be valid for such material used in combination with other materials or in other processes. It is intended for use by persons having technical skill, at their own discretion and risk. This information should not be used to establish specification limits nor used alone as the basis of design. Handling precaution information is given with the understanding that those using it will satisfy themselves that their particular conditions of use present no health or safety hazards and comply with applicable law. Since conditions of product use and disposal are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information. As with any product, evaluation under end-use conditions prior to specification is essential. Nothing herein is to be taken as a license to operate or a recommendation to infringe on patents.

CAUTION: Do not use DuPont materials in medical applications involving implantation in the human body or contact with internal body fluids or tissues unless the material has been provided from DuPont under a written contract or other acknowledgement that is consistent with the DuPont policy regarding medical applications and expressly acknowledges the contemplated use. For further information, please contact your DuPont representative.

DuPont's sole warranty is that our products will meet our standard sales specifications in effect at the time of shipment. Your exclusive remedy for breach of such warranty is limited to refund of purchase price or replacement of any product shown to be other than as warranted. TO THE FULLEST EXTENT PERMITTED BY APPLICABLE LAW, DUPONT SPECIFICALLY DISCLAIMS ANY OTHER EXPRESS OR IMPLIED WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE, MERCHANTABILITY, OR NON-INFRINGEMENT. DUPONT DISCLAIMS LIABILITY FOR ANY SPECIAL, INCIDENTAL, OR CONSEQUENTIAL DAMAGES.

DuPont™, the DuPont Oval Logo, and all trademarks and service marks denoted with ™, SM or ® are owned by affiliates of DuPont de Nemours, Inc. unless otherwise noted.